

S-C-E203A-00-I-P (3.6mm)

3MP IR Bullet Camera



Features

- ❖ 1/ 2.9" CMOS sensor
- ❖ Starlight Effect
- ❖ Ingress Protection: IP66
- ❖ 18 infrared lights, the maximum fill light distance is 30m



Technical Specifications

Model		S-C-E203A-00-I-P(3.6mm)
Major Specifications		
Camera	Image sensor	1/ 2.9" CMOS
	Maximum Resolution	2304*1296
	Effective Pixels	3.0MP
	Supported resolution	2304*1296/1920*1080/1280*960/1280*720/960*540/720*576/704*576/640*480/640*360/512*288
	Video Compression Standard	H.265/H.264
	Frame Rate	3.0MP@25fps
	ROM/RAM	8MB/64MB
	code stream	Dual Stream
	Video Steam	Support VBR,CBR
	Focal length	3.6mm
	Max Aperture	F2.0
	Lens aperture type	Fixed iris
	Angle of view	H 79.6°, V 47.7°, D: 97.8°
	IR range	30m
	Infrared light	14μ x 18
Minimum illumination	Color:0.01 Lux B/W:0 Lux(IR ON)	
Function	Motion Detection	Support
	Email Alert	Support
	Image Rotation	support (mirror/flip)
	Wide Dynamic	DWDR
	SD card	Not Support
	External Audio Input	Support
Network	Ethernet	10M/100M Ethernet, RJ45 port
	protocol	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
	ONVIF	ONVIF 2.4(Profile S)
	WEB Interface	Support Chinese/English

General Specifications	
Power type	12V DC and PoE (IEEE 802.3af)
Power consumption	Day ≤2W Night ≤8W
Operating temperature	-20°C to +60°C
Operating humidity	10% to 90% (non-condensing)
IP rating	IP66
Weight	390g
Dimensions	φ69x185mm
Material	Aluminum alloy



Dimensions

