

## S-C-E3050-00-I-P (2.8mm)

5MP IR Dome Camera

Indoor Application



### Features

- ❖ 1/3" CMOS sensor
- ❖ DC12V/2A, PoE (IEEE 802.3af)
- ❖ Ingress Protection: IP66
- ❖ 18 infrared lights, the maximum fill light distance is 20m



## Technical Specifications

Model		S-C-E305A-00-I-P(2.8mm)
Major Specifications		
Camera	Image sensor	1/ 3" CMOS
	Maximum Resolution	2560*1792
	Effective Pixels	5.0MP
	Supported resolution	2560*1792/2560*1440/2048*1440/1920*1080/1280*960/1280*720/960*540/768*432/720*576/720*480/704*576/640*480/512*288/352*288
	Video Compression Standard	H.265/H.264
	Frame Rate	5.0MP@25fps
	ROM/RAM	8MB/128MB
	Code Stream	Dual Stream
	Video Steam	Support VBR,CBR
	Focal length	2.8mm
	Max Aperture	F2.0
	Lens aperture type	Fixed iris
	Angle of view	H 92.5°, V 59.9°, D: 108.5°
	IR range	20m
	Infrared light	14μ x 18
Minimum illumination	Color:0.01 Lux B/W:0 Lux(IR ON)	
Function	Motion Detection	Support
	Email Alert	Support
	Image Rotation	support (mirror/flip)
	Wide Dynamic	DWDR
	SD card	Not Support
	External Audio Input	Support
Network	Ethernet	10M/100M Ethernet, RJ45 port
	protocol	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
	ONVIF	ONVIF 2.4(Profile S)
	WEB Interface	Support Chinese/English

General Specifications	
Power type	12V DC and PoE (IEEE 802.3af)
Power consumption	Day ≤3W Night ≤7W
Operating temperature	-20°C to +60°C
Operating humidity	10% to 90% (non-condensing)
IP rating	IP66
Vandal-Proof grade	IK10
Weight	500g
Dimensions	φ120x86.5 mm
Material	Aluminum alloy and Polycarbonate



## Dimensions

